

AC SUMBERSIBLE PUMPS

Sales: Lindy Mazibuko
+27 81 810 8305 | lindy@jbhsolar.co.za



TECHNICAL SPECIFICATIONS

	SP30/0,37KW	SP40/0,55KW	SP51/0,75KW	SP68/1,1KW	SP110/1,1KW
Impeller	Plastic	Plastic	Plastic	Plastic	Plastic
Working Voltage (V)	220V	220V	220V	220V	220V
Max. Flow(m ³ /h)	9.0	9.0	9.0	9.0	5.0
Max. Head (m)	30	40	51	68	110
Outlet (Inch)	1.0"/1.5"	1.0"/1.5"	1.0"/1.5"	1.0"/1.5"	1.0"/1.5"
Pump Diameter (mm)	88	88	88	88	88
Power (KW)	0.37	0.55	0.75	1.1	1.1
Power (HP)	0.55	0.75	1.0	1.5	1.5

PERFORMANCE DATA

Model	Delivery (RPM = 2850 r/min)										
	Q m ³ /h	0	1	2	3	4	5	6	7	8	9
	Q L/min	0	17	33	50	67	83	100	117	133	150
SP30/0.37KW	Head(m)	30	29	27	26	25	20	17	14	10	5
SP40/0.55KW		42	40	38	36	35	29	24	20	14	7
SP51/0.75KW		54	51	49	46	45	37	31	25	18	9
SP68/1.1KW		71	68	65	61	58	49	42	34	23	12
SP110/1.1KW		117	110	105	90	75	50	-	-	-	-